

23 April 2014

ASX ANNOUNCEMENT

Goldphyre Resources Limited

ACN: 149 390 394

ASX: GPH Shares on Issue: 50,732,010 Total Shares Quoted on ASX: 50,732,010 Listed options on issue: 28,910,670 Unlisted Options on Issue: 21,389,800 Market Cap @ 3.0cps - \$1.5m Cash - \$0.72m (at 31/03/2014)

Board and Management:

Ron Punch – Executive Chairman Brenton Siggs – Non Executive Technical Director Chris Clegg – Non Executive Director John Ribbons – Company Secretary

Street Address: 37 Colin Street, West Perth, WA 6005 Australia

Postal Address: PO Box 1941 West Perth, WA, 6872 Australia

Tel: +61 8 9422 9502 Fax: +61 8 9389 2199

Email: info@goldphyre.com.au Web: www.goldphyre.com.au

Projects:

Lake Wells: gold, nickel, base metals, PGE, uranium Laverton Downs: gold, base metals Gambier Lass: gold, base metals Kilkenny: gold, base metals Iguana: gold, base metals Yamarna: gold, PGE, uranium Mailman Hill: gold, base metals



"Targeting large new gold and base metal deposits in overlooked and underexplored greenstone belts in Western Australia"

ACTIVITIES REPORT - FOR THE QUARTER ENDING 31 MARCH 2014

SUMMARY and HIGHLIGHTS

- Follow-up Rotary Air Blast (RAB) drill program completed at the Laverton Downs project (34 holes totaling 1,716 metres) confirms shallow gold-in-drillhole anomaly
 - +100 ppb gold-in-drillhole anomaly interpreted +700 metres long and open at depth and to the north
 - > Encouraging composite gold intercepts recorded including:
 - > 8m @ 0.40 g/t gold from 16m (LDRB053)
 - 12m @ 0.30 g/t gold from 28m (LDRB044)
 - 20m @ 0.18 g/t gold from 20m (LDRB074)
- One metre split samples from anomalous Laverton Downs gold intervals collected and awaiting results

EXPLORATION PLANNED FOR JUNE 2014 QUARTER

- RAB/AC drill program (circa 4,500m) at Lake Wells Project planned for Axford gold prospect (where intersections include 6m @ 3.46g/t Au, 48m @ 0.52g/t Au and 10m @ 1.55g/t Au, previously reported) and regional targets. The Lake Wells Project is located to the north of Gold Road Resources' (ASX: GOR) significant gold mineralisation reports from the Dorothy Hills Trend
- RC drilling at Lake Wells Project to follow interpretation of RAB/AC drill program results
- Follow-up RAB drilling at Laverton Downs to extend the existing drill-hole gold anomaly
- Follow-up soil geochemistry planned to define the extent of gold anomalous zones at Mailman Hill
- Follow-up rock chip and soil geochemistry planned for gold targets on the Kilkenny Project

Goldphyre Resources Limited (ASX: GPH, Goldphyre or the Company) is pleased to present the following report on activites for the quarter ending 31 March 2014.



LAKE WELLS PROJECT - 100% Goldphyre Resources Limited

Fieldwork during the March 2014 Quarter included field reconnaissance, gridding and checking historic drillholes.

Heavy rain events throughout the Eastern Goldfields and particularly the North Eastern Goldfields in the reporting period have delayed the commencement of drilling at the Lake Wells Project.


Exploration planned for the June 2014 Quarter includes AC drilling at the Axford Prospect in the northwestern area of the Lake Wells Project, along with reconnaissance RAB/AC drilling in the central and southeastern parts, to follow up Goldphyre and historic geochemistry and AC drill hole anomalies as described in the September 2013 Quarterly report (Figure 1).

The AC drilling in the Axford prospect area will target untested along trend gold potential of previous AC and RC drilling by the Company and also test across a small playa (salt) lake that is yet to be drill tested and lies immediately east of the main trend of Axford Prospect RC drilling.

Additional reconnaissance AC drilling is aimed at testing anomalous calcrete samples (9 and 16 ppb Au) in conjunction with elevated fine-fraction soil sample results up to 4 ppb gold (GPH ASX Quarterly Report September 2013 Quarter, dated 29/10/2013*) in the southeastern part of the Lake Wells Project. This drill target is further supported by recent previous explorers' data acquisition showing historic end-of-hole gold anomalism¹ to the south of the project area, coupled with the reported success of neighboring explorer Gold Road Resources' (ASX:GOR) geophysical (SAM) survey targeting (GOR ASX Announcement 14/08/2013). This prospective section of the Lake Wells Project is located approximately 60km from Gold Road Resources' Gruyere Prospect.

Follow-up Reverse Circulation (RC) drilling at the Lake Wells Project and the Axford Prospect will commence to test any anomalies generated in the RAB/AC drilling programme.

Figure 1. Lake Wells EAST Area (E38/2505) Geochemistry and Targets with TMI Magnetics basemap showing elevated gold, PGE, copper and zinc values from 2012 drilling (GPH ASX Announcement, 3/09/2013)



¹A72218. Vinar, J, 2005. Yamarna Group 1 Annual Report E38/610, E38/1567 and P38/3169. Terra Gold Mining Limited, page 3.



LAVERTON DOWNS PROJECT - 100% Goldphyre Resources Limited

Goldphyre reported encouraging anomalous composite gold results from the follow-up RAB drilling program (34 holes, 1716 metres) at its 100% owned Laverton Downs Project during the March 2014 Quarter. The Laverton Downs project is situated in the central part of the prospective Laverton Tectonic Zone which is host to several significant gold deposits².

The first round of shallow RAB drilling completed by Goldphyre in late 2013 demonstrated significant gold mineralisation in the area of historic gold anomalies (up to 0.9 g/t gold³, GPH ASX Release 15/11/2013*).

The recent follow-up drilling also targeted along trend potential of the high-grade intercept of 3m @ 10.17 g/t Au from 23m in LDRB025 (GPH ASX Release 22/01/2014*). This shallow, high grade gold intercept remains open at depth.

Table 1. Drill Status Table

Hole ID	Drill Type	Project	Holes	Metres
LDRB043-076	RAB	Laverton Downs	34	1716

The recent follow-up RAB drilling in January-February, 2014 was completed on 40m-160m spaced drill lines focussed mainly to the north of significant gold intercepts in LDRB025 and LDRB030 and has extended the interpreted gold-inhole anomaly to approximately 700 metres (Appendix 1).

The north north-easterly trending gold anomaly is interpreted to extend beneath several RAB holes that failed to penetrate flat lying Permian(?) cemented sandstone (anomalous gold-in-drillhole trend through LDRB025-LDRB055-LDRB053-LDRB038, Figure 2) and is open to the north. An interpreted southerly trending gold in drillhole anomaly (LDRB030-LDRB044) also remains open to the south.


Hole	Hole Type	Northing(m)	Easting(m)	RL	Dip	Azimuth	Interv	al	Width(m)	Gold (g/t)	Hole Depth (m)
							From (m)	To(m)			
LDRB044	RAB	6853120	444242	486	60	270	28	40	12	0.30	65
LDRB049	RAB	6853240	444020	480	60	270	16	24	8	0.19	36
							35	36	1	0.20	
LDRB053	RAB	6853400	444120	486	60	270	16	24	8	0.40	43
LDRB055	RAB	6853240	444060	486	60	270	20	24	4	0.17	47
							28	36	8	0.28	
LDRB057	RAB	6853080	444000	484	60	270	40	44	4	0.20	
LDRB073	RAB	6853200	444010	487	60	270	20	28	8	0.24	47
							36	40	4	0.15	
LDRB074	RAB	6853200	444050	487	60	270	20	40	20	0.18	44


Table 2. Laverton Downs Drill-Hole Composite Assay Results

² Website references: www.anglogold.com, www.portergeo.com.au/database/mineinfo, www.regisresources.com.au

³ A20641. Annual Technical Report. Laverton Downs Project. Exploration Licences 38/5,38/37, Prospecting Licences 38/457, 38/458, Mineral Claim 38/7984 for the period 1/1/86-31/12/86. Hillmin Gold Mines Pty Ltd. 1986







The anomalous gold intercepts are associated with shearing and quartz veining hosted by schistose mafic rocks and intermediate volcanic rocks.



FURTHER EXPLORATION PLANNED

Follow-up RAB drilling at Laverton Downs is planned following scheduled RAB/AC drilling at the Lake Wells Project in the June 2014 quarter.

KILKENNY PROJECT - 100% Goldphyre Resources Limited

Kilkenny Project tenure was granted in the December 2013 quarter, and a Program of Work-Exploration (PoW-E) has been lodged with the Department of Mines and Petroleum (DMP) to facilitate future RAB/AC drill targeting.

Further fieldwork will include soil/geochemistry sampling over previous explorers' gold-in-soil anomalies (including a +150 ppb soil spot value⁴) to highlight geochemistry gold anomalies to refine targets for reconnaissance RAB/AC drill testing.

ISLAND VIEW PROJECT – 100% Goldphyre Resources Limited

An AC drill program planned on Lake Cowan in the report period was postponed to the June 2014 quarter following heavy rain events in the Eastern Goldfields and poor lake access for track drilling rigs. As a result, no fieldwork was completed on the Island View Project.

IGUANA PROJECT - 100% Goldphyre Resources Limited

No fieldwork was completed on the Iguana Project. A Program of Work-Exploration (PoW-E) has been lodged with the Department of Mines and Petroleum (DMP) to facilitate future RAB/AC drill targeting.

Previous explorers' compilation work in the March 2014 quarter has revealed a number of near surface (0-5m depth), strongly anomalous gold values recorded in shallow RAB drilling on the southern boundary of the tenement and this area requires further geochemistry/RAB drill testing.

YAMARNA PROJECT - 100% Goldphyre Resources Limited

No fieldwork was completed on the Yamarna Project in the reporting period. Following a review of the project, the Company is seeking expressions of interest for joint venture or farm-in opportunities.

TENEMENTS

No tenement applications were granted in the March 2014 quarter.

Following recent drill testing in the December 2013 quarter and a detailed review of exploration results, the Gambier Lass Project was considered low prospectivity and subsequently all Gambier Lass tenure was surrendered in the March 2014 quarter.

⁴A57289. Howland, JP, 1998. Mount Kersey Mining NL C373/1994 Murrin Murrin project. Joint Annual Report for the period 13 September 1997 to 12 September 1998.



FURTHER WORK PLANNED – JUNE 2014 QUARTER

During the June 2014 quarter the following activities are planned:

- Follow-up and reconnaissance RAB/AC drill programs (circa 4,500m) at Lake Wells planned (including Axford trend where intersections include 6m @ 3.46g/t Au, 48m @ 0.52g/t Au and 10m @ 1.55g/t Au, GPH ASX Release 12/12/2012*) and regional targets. The Lake Wells Project is not far from where Gold Road Resources (ASX: GOR) has been reporting significant gold mineralisation from the Dorothy Hills Trend
- Follow-up soil geochemistry planned to define the extent of gold anomalous zones at Mailman Hill
- Rockchip and soil geochemistry planned with follow-up RAB/AC drilling of priority targets on the Kilkenny Project

CORPORATE CASH POSITION

As at 31 March 2014, the Company had cash reserves of approximately \$0.72 million.

Contact: Brenton Siggs Technical Director Goldphyre Resources Limited

Ph (08) 9422 9502

* In accordance with Listing Rule 5.23.2, the Company confirms in the subsequent public report that it is not aware of any new information or data that materially affects the information included in the relevant market announcement and, in the case of estimates of mineral resources or ore reserves, that all material assumptions and technical parameters underpinning the estimates in the relevant market announcement continue to apply and have not materially changed.

COMPETENT PERSONS STATEMENT

The information in this report that relates to Exploration results, Mineral Resources or Ore Reserves is based on information compiled by Mr Brenton Siggs who is a member of the Australasian Institute of Geoscientists. Mr Siggs is contracted to the Company through Reefus Geology Services and is a Non-Executive Director (Exploration Manager) of Goldphyre Resources Limited. Mr Siggs has sufficient experience relevant to the style of mineralisation and type of deposit under consideration and to the activity currently being undertaken to qualify as a Competent Person as defined in the 2012 edition of the 'Australian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves'. Mr Siggs consents to the inclusion in this report of the matters based on his information in the form and context in which it appears. Mr Siggs is a shareholder and director of Goldphyre WA Pty Ltd, a company that holds ordinary shares and options in the capital of Goldphyre Resources Limited (Goldphyre Resources Limited, Annual Report 2013).

FORWARD LOOKING STATEMENT DISCLAIMER

This announcement contains forward-looking statements which involve a number of risks and uncertainties. These forward looking statements are expressed in good faith and believed to have a reasonable basis. These statements reflect current expectations, intentions or strategies regarding the future and assumptions based on currently available information. Should one or more of the risks or uncertainties materialise, or should underlying assumptions prove incorrect, actual results may vary from the expectations, intentions and strategies described in this announcement. No obligation is assumed to update forward looking statements if these beliefs, opinions and estimates should change or to reflect other future developments.



APPENDIX 1 – DRILL COLLAR DATA (All gold intercepts >0.10 g/t gold reported in Table 2)

Project	Hole	Hole Type	Northing(m)	Easting(m)	RL	Dip	Azimuth	Hole Depth (m)
	LDRB043	RAB	6853160	444280	486	60	270	44
	LDRB044	RAB	6853120	444242	486	60	270	65
	LDRB045	RAB	6853240	444140	478	60	270	49
	LDRB046	RAB	6853244	444180	480	60	270	25
	LDRB047	RAB	6853242	444220	490	60	270	19
	LDRB048	RAB	6853240	443980	476	60	270	56
	LDRB049	RAB	6853240	444020	480	60	270	36
	LDRB050	RAB	6853400	444000	481	60	270	57
	LDRB051	RAB	6853402	444040	480	60	270	46
	LDRB052	RAB	6853400	444080	482	60	270	45
	LDRB053	RAB	6853400	444120	486	60	270	43
	LDRB054	RAB	6853400	444160	488	60	270	50
	LDRB055	RAB	6853240	444060	486	60	270	47
	LDRB056	RAB	6853240	444100	486	60	270	44
SL	LDRB057	RAB	6853080	444000	484	60	270	47
IMO	LDRB058	RAB	6853560	443880	486	60	270	49
Ď	LDRB059	RAB	6853556	443920	484	60	270	62
Laverton Downs	LDRB060	RAB	6853555	443960	484	60	270	54
Ive	LDRB061	RAB	6853560	444000	486	60	270	59
	LDRB062	RAB	6853560	444045	482	60	270	54
	LDRB063	RAB	6853560	444082	482	60	270	45
	LDRB064	RAB	6853560	444160	486	60	270	25
	LDRB065	RAB	6853630	444090	488	60	270	44
	LDRB066	RAB	6853720	443860	484	60	270	70
	LDRB067	RAB	6853715	443900	484	60	270	66
	LDRB068	RAB	6853715	443940	483	60	270	53
	LDRB069	RAB	6853718	443980	484	60	270	69
	LDRB070	RAB	6853720	444020	483	60	270	74
	LDRB071	RAB	6853720	444060	483	60	270	78
	LDRB072	RAB	6854040	443960	491	90	0	36
	LDRB073	RAB	6853200	444010	487	60	270	47
	LDRB074	RAB	6853200	444050	487	60	270	44
	LDRB075	RAB	6853000	443910	485	60	270	62
	LDRB076	RAB	6853000	443950	485	60	270	52



APPENDIX 2 - TENEMENT SCHEDULE – 31 MARCH, 2014

Project	Tenement	Location	Interest at beginning of quarter	Acquired / Disposed	Interest at end of quarter
Iguana	E16/447	Ora Banda, WA	100	NA	100
Island View	E15/1049	Higginsville, WA	100	NA	100
Island View	E15/1050	Higginsville, WA	100	NA	100
Island View	P15/5647	Higginsville, WA	100	NA	100
Kilkenny	E39/1702	Leonora,WA	100	NA	100
Kilkenny	P39/5310	Leonora,WA	100	NA	100
Kilkenny	P39/5311	Leonora,WA	100	NA	100
Kilkenny	P39/5312	Leonora,WA	100	NA	100
Kilkenny	P39/5313	Leonora,WA	100	NA	100
Kilkenny	P39/5314	Leonora,WA	100	NA	100
Kilkenny	P39/5315	Leonora,WA	100	NA	100
Kilkenny	P39/5316	Leonora,WA	100	NA	100
Kilkenny	P39/5317	Leonora,WA	100	NA	100
Kilkenny	P39/5318	Leonora,WA	100	NA	100
Kilkenny	P39/5319	Leonora,WA	100	NA	100
Kilkenny	P39/5320	Leonora,WA	100	NA	100
Kilkenny	P39/5321	Leonora,WA	100	NA	100
Kilkenny	P39/5322	Leonora,WA	100	NA	100
Kilkenny	P39/5323	Leonora,WA	100	NA	100
Kilkenny	P39/5324	Leonora,WA	100	NA	100
Kilkenny	P39/5325	Leonora,WA	100	NA	100
Kilkenny	P39/5326	Leonora,WA	100	NA	100
Kilkenny	P39/5327	Leonora,WA	100	NA	100
Kilkenny	P39/5328	Leonora,WA	100	NA	100
Kilkenny	P39/5329	Leonora,WA	100	NA	100
Kilkenny	PLA39/5472	Leonora,WA	100	NA	100
Kilkenny	PLA39/5473	Leonora,WA	100	NA	100
Kilkenny	PLA39/5474	Leonora,WA	100	NA	100
Lake Wells	E38/1903	Laverton, WA	100	NA	100
Lake Wells	E38/2113	Laverton, WA	100	NA	100
Lake Wells	E38/2114	Laverton, WA	100	NA	100
Lake Wells	E38/2505	Laverton, WA	100	NA	100
Lake Wells	ELA 38/2901	Laverton, WA	100	NA	100
Laverton Downs	E38/2724	Laverton, WA	100	NA	100
Mailman Hill	E37/990	Leonora,WA	100	NA	100
Mailman Hill	P37/7877	Leonora,WA	100	NA	100
Yamarna	E38/1949	Laverton, WA	100	NA	100



APPENDIX 3 - REPORTING OF EXPLORATION RESULTS - JORC (2012) REQUIREMENTS

SECTION 1: SAMPLING TECHNIQUES AND DATA- LAVERTON DOWNS PROJECT

Criteria	JORC Code Explanation	Commentary
Sampling techniques	 Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. 	 LAVERTON DOWNS PROJECT - No geochemistry samples collected.
	 Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. 	
	 Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information. 	
Drilling techniques	 Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc). 	 Rotary Air Blast (RAB) drilling completed by Challenge Drilling, Kalgoorlie-Boulder. RAB blade and RAB hammer bit achieved hole diameter size of 104mm (4 ¼ inch).
Drill sample recovery	 sample recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred 	 Sample recovery size and sample condition (dry, wet, moist) recorded. Drilling with care (eg. clearing hole at start of rod, regular cyclone cleaning) if water encountered to reduce incidence of wet samples. Insufficient sample population to determine whether relationship exists between sample
Logging	 due to preferential loss/gain of fine/coarse material. Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. 	 recovery and grade. Logging carried by inspection of washed cuttings at time of drilling with end-of-hole (EOH) samples and any unusual lithologies collected in plastic chip trays for future reference.
	 The total length and percentage of the relevant intersections logged. 	



Criteria	JORC Code Explanation	Commentary
Sub-sampling techniques and sample preparation	• If core, whether cut or sawn and whether quarter, half or all core taken.	No core drilling
	 If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. For all sample types, the nature, quality and appropriateness of the sample preparation technique. Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples. Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling. Whether sample sizes are appropriate to the grain size of the material being sampled. 	 Composite and one metre end of hole (EOH) samples (1-4 metres) were collected by PVC spear or aluminium scoop in pre-numbered calico bags. Sample weight 2 - 3 kg. Wet samples bagged separately in plastic bags prior to placing in plastic and/or polyweave bags for despatch to assay laboratory. Scoop used for wet sample collection. All samples are pulverised utilising Essa LM1, LM2 or LM5 grinding mills determined by the size of the sample. Samples are dried (nominal 110 degrees C), crushed and pulverized to produce a homogenous representative sub-sample for analysis.A grind quality target of 85% passing 75µm has been established and is relative to sample size, type and hardness. Field duplicates collected as part of QA/QC process which also involved the use of two STANDARD samples (supplied by ORE Pty Ltd, Melbourne) and one BLANK sample
Quality of assay data and laboratory tests	 The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc. Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established. 	 (supplied by ORE Pty Ltd, Melbourne). The samples were collected for gold and multielement analysis and this analysis work was completed at MINAnalytical, Perth. Following the Sample Preparation outlined in the previous section above, samples were assayed with Lab Code FA50AAS and method. This technique involves a 50g Fire Assay for gold with AAS finish. Gold intercepts calculated with primary Au gold values with Au1 repeat values excluded. Gold intercepts calculated with lower cut 0.10 g/t Au, no upper cut, 4m (one composite sample) internal dilution. For multielement suite - (Lab Code AR2510) elements including (but not limited to; Ag, As, Co, Cu, Fe, Mn, Ni, V, Zn). Aqua Regia Digest is an economical and effective total digest analysis technique for target elements. Inductively coupled plasma mass spectrometry (ICP-MS) is also recognised as an effective, reasonably priced technique for low level gold and base metal detection. Quality control process and internal laboratory checks demonstrate acceptable



Criteria	JORC Code Explanation	Commentary
Verification of sampling and assaying	 The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. 	 QA/QC procedures include certified Standard Sample(s), a Blank sample and a field duplicate submitted to the Assay Laboratory with the field samples as described above. The Ratio of Standards/ Blanks/Duplicates in the soil sampling program is 1 in approximately every 25 field samples. Internal laboratory standards are completed as a matter of course. Sample data was captured in the field and data entry completed in the Company's Perth office. Sample data was then loaded into the Company's DATASHED database and validation checks completed to ensure data
Location of data points	 Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. Specification of the grid system used. Quality and adequacy of topographic control. 	 accuracy. Drill collars were surveyed by handheld Garmin 60 GPS with horizontal accuracy (Easting and Northing values) of +-5m. Grid System – MGA94 Zone 51. Topographic elevation using published GSWA geological maps and hand held GPS with Z range +-15m suitable for relatively flat terrain.
Data spacing and distribution	 Data spacing for reporting of Exploration Results. Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. Whether sample compositing has been applied. 	 Hole spacing on 40-80m spaced east- west drill traverses to followup along trend potential of recent Goldphyre (ASX Announcement dated 22nd January, 2014)and historic gold-in-hole RAB drill anomalies and historic gold soil geochemistry anomalies.
Orientation of data in relation to geological structure	 Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	 East-west drill traverses considered effective to intersect interpreted north to north north west striking structures and Archaean rock sequence.
Sample security	• The measures taken to ensure sample security.	 Samples collected from the field delivered by field team direct to drop off point in Kalgoorlie for despatch to Perth lab.
Audits or reviews	• The results of any audits or reviews of sampling techniques and data.	No audits or reviews completed on this batch of samples.



Section 2: REPORTING OF EXPLORATION RESULTS - LAVERTON DOWNS PROJECT

Criteria	JORC Code Explanation	Commentary
Mineral tenement and land tenure status	 Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area. 	 The LAVERTON DOWNS PROJECT, located 15 km north of Laverton, Western Australia consists of tenement: E38/2724. The tenement is held 100% by Goldphyre Resources Limited. There is no Native Title Claim registered in respect of the project tenure. Accordingly, there is no requirement for a Regional Standard Heritage Agreement to be signed. The tenement has an expiry date of 17/1/2018.
Exploration done by other parties	• Acknowledgment and appraisal of exploration by other parties.	 Previous shallow reconnaissance RAB drilling and auger sampling has been completed on much of the project area, with a focus on the northern portion. Companies that have completed previous exploration in the region include Delta Gold Ltd, CRA Exploration Pty Ltd and Ashton Gold (WA) Ltd.
Geology	 Deposit type, geological setting and style of mineralisation. 	 Target is shear hosted gold mineralisation associated with the interpreted north north west trending Admiral Hill Shear. Other target types are Volcanic Hosted Massive Sulphide (VHMS) Cu-Zn mineralisation and ultramafic Ni hosted mineralisation.
Drill hole Information	 A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: easting and northing of the drill hole collar elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar dip and azimuth of the hole down hole length and interception depth hole length. If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent	 This is the second phase of RAB drilling completed by Goldphyre Resources Limited. Collar information for the drill holes is included in Appendix 1.



Criteria	JORC Code Explanation	Commentary
Data aggregation methods	 In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated. Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. The assumptions used for any reporting of metal equivalent values should be clearly stated. 	 Intercepts are reported as down-hole length (whole metres in the case of RAB, AC and RC drilling) and average metal or element intercept values > 0.10 g/t Au. Where present, higher grade values are included in the intercepts table and assay values > 1.0 g/t Au have been stated on a separate line below the intercept assigned with the text 'includes'. No metal equivalent values or formulas used.
Relationship between mineralisation widths and intercept lengths	 These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this 	 All results are based on whole down-hole metres.
Diagrams	 effect (eg 'down hole length, true width not known'). Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views. 	 Appropriate summary diagrams with Scale and North Point shown is/are included in the accompanying report above.
Balanced reporting	Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.	 All gold (>0.15 g/t Au) values for the samples collected are displayed in table(s) included in the accompanying report above.
Other substantive exploration data	 Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances. 	 Recent reconnaissance RAB sampling (ASX Announcements dated 13th December, 2013 and 22nd January, 2014) has assisted the recent RAB drill targeting. Drill hole collars are annotated on a geological figure in the body of the report.
Further work	 The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	 Based on results returned and Other Substantive Exploration data summarised above, the design of further RAB+-RC drill programs is justified. Diagram included in body of report.